

## Swivel Self Locking Hook 8-027

---

### Product information



- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Magnaflux crack detection is performed 100% on each batch.

... [Read more](#)

---

**Material:** Alloy Steel - Quenched and Tempered

**Marking:** According to standard

**Temperature range:** Tempering temperature minimum 400°C


**Standard:** EN 1677-3

**Safety factor:** 4:1

**Grade:** 8

## Swivel Self Locking Hook 8-027

### Blueprint



### Technical data

Part code	Code	Chain diameter mm	WLL ton	A mm	B mm	D mm	H, mm	K mm	Pmm mm	T mm	Weight kg
420500110860	YE	6	1.12	31	22	12	19	149	29	15	0.7
420500200860	YE	8	2	36	29	14	24	186	34	20	1.2
420500320860	YE	10	3.15	40	34	16	30	220	44	26	2
420500530860	YE	13	5.3	46	43	22	39	267	52	30	4.1
420500800860	YE	16	8	60	50	24	49	328	60	36	7.2
420501250860	YE	20	12.5	75	82	26	62	388	90	48	11.5
420501500860	YE	22	15	97	95	33	63	457	80	49	18.6