



Chain Block VL5 OLL Vital

Product information

Built on the standard model, with ball-bearing in the loading hook. This block has a built-in overload protection. Delivered with either a black (NB) or zinc plated (ZP) chain, but for use offshore, the ZP-model is recommended.

Material: Steel

Marking: According to standard, CE-marked, WLL, serial number

Temperature range: -10°C til +50°C

Standard: EN 13157, EN 818-7

Safety factor: 4:1

| Part Code | WLL ton | Lifting height m | a mm | b mm | c mm | g mm | Weight kg | Delivery time |
|-----------------|---------|------------------|------|------|------|------|-----------|---------------|
| 500100050300200 | 0.5 | 3 | 129 | 145 | 285 | 27 | 8.3 | 3 |
| 500100100300200 | 1 | 3 | 149 | 158 | 315 | 30 | 11.3 | 3 |
| 500100150300200 | 1.5 | 3 | 149 | 177 | 340 | 34 | 13.5 | 3 |
| 500100200300200 | 2 | 3 | 181 | 204 | 380 | 37 | 21 | 3 |
| 500100200500204 | 2 | 5 | 181 | 204 | 380 | 37 | 21 | 7 |
| 500100200800205 | 2 | 8 | 181 | 204 | 380 | 37 | 21 | 7 |
| 500100300300200 | 3 | 3 | 149 | 208 | 475 | 43 | 22 | 3 |
| 500100500300200 | 5 | 3 | 181 | 263 | 600 | 47 | 40 | 7 |
| 500100750350200 | 7.5 | 3.5 | 181 | 354 | 700 | 67 | 59 | 7 |

Blueprint

