Lifting Solutions Group
Axel Johnson International

Chain Block VL5 OLL Vital

Product information



Builds on the standard model, with ball-bearing in the loading hook. This block has a built-in overload protection. Delivered with either a black (NB) or zinc plated (ZP) chain, but for use offshore, the ZP-model is recommended.

... *Read more*

Material: Steel
Marking: According to standard, CE-marked, WLL, serial number
Temperature range: -10°C til +50°C
Standard: EN 13157, EN 818-7


Safety factor: 4:1

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Chain Block VL5 OLL Vital

Blueprint



Technical data

Part code	WLL ton	Lifting height m	a mm	b mm	c mm	g mm	Weight kg
500100050300200	0.5	3	129	145	285	27	8.3
500100051000204	0.5	10	129	145	285	27	8.3
500100050600200	0.5	6	129	145	285	27	-
500100100300200	1	3	149	158	315	30	11.3
500100100600204	1	6	149	158	315	30	11.3
500100101000200	1	10	149	158	315	30	-
500100150300200	1.5	3	149	177	340	34	13.5
500100151000200	1.5	10	149	177	340	34	-
500100200300200	2	3	181	204	380	37	21
500100200500204	2	5	181	204	380	37	21
500100200800205	2	8	181	204	380	37	21
500100200600200	2	6	181	204	380	37	-
500100201000200	2	10	181	204	380	37	-
500100300300200	3	3	149	208	475	43	22
500100301000200	3	10	149	208	475	43	-
500100500300200	5	3	181	263	600	47	40
500100500600200	5	6	181	263	600	47	-
500100501000200	5	10	181	263	600	47	-
500100750350200	7.5	3.5	181	354	700	67	59

© November 2026 - All Rights Reserved