



## Chain Block VL5 OLL Vital

### Product information

Builds on the standard model, with ball-bearing in the loading hook. This block has a built-in overload protection. Delivered with either a black (NB) or zinc plated (ZP) chain, but for use offshore, the ZP-model is recommended.

**Material:** Steel

**Marking:** According to standard, CE-marked, WLL, serial number

**Temperature range:** -10°C til +50°C

**Standard:** EN 13157, EN 818-7

**Safety factor:** 4:1

| Part code       | WLL<br>ton | Lifting height<br>m | a<br>mm | b<br>mm | c<br>mm | g<br>mm | Weight<br>kg | Delivery time |
|-----------------|------------|---------------------|---------|---------|---------|---------|--------------|---------------|
| 500100050300200 | 0.5        | 3                   | 129     | 145     | 285     | 27      | 8.3          | 3             |
| 500100100300200 | 1          | 3                   | 149     | 158     | 315     | 30      | 11.3         | 3             |
| 500100150300200 | 1.5        | 3                   | 149     | 177     | 340     | 34      | 13.5         | 3             |
| 500100200300200 | 2          | 3                   | 181     | 204     | 380     | 37      | 21           | 7             |
| 500100200500204 | 2          | 5                   | 181     | 204     | 380     | 37      | 21           | 7             |
| 500100200800205 | 2          | 8                   | 181     | 204     | 380     | 37      | 21           | 7             |
| 500100300300200 | 3          | 3                   | 149     | 208     | 475     | 43      | 22           | 7             |
| 500100500300200 | 5          | 3                   | 181     | 263     | 600     | 47      | 40           | 3             |
| 500100750350200 | 7.5        | 3.5                 | 181     | 354     | 700     | 67      | 59           | 7             |

Blueprint

