



## Fall Arrest Block IKAR HWPB with Webbing

### Product information

Robust, low-maintenance fall arrest device with webbing and swivel. The swivel prevents the webbing from twisting. Internal energy-absorber and hook with fall indicator.

Low weight thanks to extra light plastic housing.

Approved for vertical and horizontal use.

**Edge tested:** Tested at sharp edges,  $R \geq 0,5$  mm (CNB/P/11.060 2008 sharp edge Type A)

**Carabiner:** IKAR IKV11 (Lk = 137 mm) Small swivel snap hook (opening  $\varnothing$  25 mm).

The blocks can be delivered with the following approvals: ANSI/ASSE Z 359.14-2014/LE up on request.

**Material:** Body: plastic, webbing: Dyneema®

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C to +50°C.

**Standard:** EN 360

Part Code	Code	Max. number of persons	Length m	Max load kg	Dimensions mm	L mm	B mm	T mm	Weight kg	Delivery time
822100350630	HWPB 3.5	1	3.5	136	326 x 104 x 78	326	104	78	1.2	3
822100550630	HWPB 5.5	1	5.5	136	300 x 130 x 78	300	130	78	1.5	7
822100700630	HWPB 7	1	7	136	300 x 165 x 80	300	165	80	1.8	3
822100900630	HWPB 9	1	9	136	335 x 168 x 88	355	168	88	2.3	3
822101200630	HWPB 12	1	12	136	370 x 195 x 95	370	195	95	3.4	3
822101500630	HWPB 15	1	15	136	400 x 195 x 95	400	195	95	4.8	3

# Blueprint

