



## Fall Arrest Block IKAR HWPS/E

### Product information

Robust, retractable fall arrest device from IKAR either delivered with galvanized- (HWPS) or stainless-steel wire and swivel (HWPS-E). The device has an internal energy-absorber and hook with fall indicator, and the plastic housing makes its weight and maintenance low.

Approved for vertical and horizontal use.

**Edge tested:** Tested at sharp edges,  $R \geq 0,5$  mm (CNB/P/11.060 2008 sharp edge Type A)

**Carabiner:** IKAR IKV21 (Lk = 186mm) small swivel snap hook (opening  $\varnothing$  26 mm)

Can be delivered with other carabiners or scaffolding hooks up on request.

The blocks can be delivered with the following approvals: ANSI/ASSE Z 359.14-2014/LE up on request.

**Material:** Body: Plastic

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C to +50°C.

**Standard:** EN 360

Part code	Code	Max. number of persons	Length m	Description	Max load kg	L	B,	T mm	Weight kg
822100300640	HWPS 3	1	3	Galvanized wire	136	390	104	78	1.9
822100600640	HWPS 6	1	6	Galvanized wire	136	420	145	80	2.5
822100900640	HWPS 9	1	9	Galvanized wire	136	460	168	88	3.2
822101200640	HWPS 12	1	12	Galvanized wire	136	500	195	95	4.9
822101200641	HWPS12E	1	12	Stainless steel wire	136	500	195	95	4.9
822101800640	HWPS 18	1	18	Galvanized wire	136	540	220	97	6.3
822102400640	HWPS 24	1	24	Galvanized wire	136	570	250	97	7.3

## Blueprint

