Lifting Solutions Group
Axel Johnson International

Female Double Swivel Ring Codipro SS FE DSR

Product information



SS FE DSR M Stainless steel female double swivel ring.

The stainless steel version of the double swivel ring, FE.DSR, can be used in humid, corrosive, chemical, maritime environment. Its double articulation allows it to line up perfectly with the sling.

Features:

- Rotatable under load.

... *Read more*

Material: AISI 316 L
Marking: According to standard, CE-mark
Temperature range: -20°C up to + 200°C
Standard: EN 1677-1
except grade/WLL


Safety factor: 5:1

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Female Double Swivel Ring Codipro SS FE DSR

Blueprint



Technical data

Part code	WLL ton	Thread	Torque Nm	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	L max. mm	S mm	Weight kg
4215SSFEDSRM8	0.3	M 8 (x1,25)	6	43	40	45	53	38	17	76	13	43	20	0.9
4215SSFEDSRM10	0.5	M 10 (x1,50)	10	43	40	45	53	38	17	76	13	43	20	0.9
4215SSFEDSRM12	0.8	M 12 (x1,75)	15	43	40	45	53	38	17	76	13	43	20	0.9
4215SSFEDSRM14	1	M 14 (x2)	30	43	40	45	53	38	17	76	13	43	20	0.9
4215SSFEDSRM16	1.4	M 16 (x2)	50	43	40	45	53	38	17	76	13	43	20	0.9
4215SSFEDSRM18	1.4	M 18 (x2,5)	70	62	55	58	83	56	25	115	19	62	24	2.6
4215SSFEDSRM20	1.4	M 20 (x2,5)	100	62	55	58	83	56	25	115	19	62	24	2.6
4215SSFEDSRM22	2.2	M 22 (x2,5)	120	62	55	58	83	56	25	115	19	62	24	2.6

© November 2026 - All Rights Reserved