

Lashing Chain Powertex PLC

Product information





Powertex Lashing chains PLC are made of high strength Grade 8 round steel chains and latch hooks at each end.

The chains are designed to allow quick and safe hooking to the trailer and/or to the load to be secured.

- Safe Powertex Lashing chains are strong and reliant and consists of EN standard compliant chains and hooks
- Lashing chains are made to EN 12195-3
- Black electrophoretic painted chains Grade 8 acc to EN 818-2
- Red powder painted clevis hooks with heavy duty latches acc to EN 1677-2
- Each lashing chain assembly is marked with a durable Aluminum Identification tag
- Intended to be used with Powertex load binder
- Multilanguage user manuals included

Material: High strength chain and hooks in Grade 8 acc to EN standard

Marking: According to standard, Powertex, Lashing capacity, "Lashing chain - Not for lifting"!, Manufacturing date, Batch number. For 2-part lashing the STF is marked on the tensioner, not on the chain!

Temperature range: -40°C up to + 200°C.

Finish: Black electrophoretic painted chains and red powder painted hooks

Standard: EN 12195-3, EN 818-2, EN 1677-2

Note: For 2-part lashing the STF is marked on the tensioner, not on the chain

Warning: Not approved for lifting.

| Part code | Chain diameter mm | LC kN | LC daN | MBL ton | EWL m | Туре | Weight kg |
|-----------------|----------------------|----------|-----------|------------|----------|-------|--------------|
| 704100800500090 | 8 | 40 | 4,000 | 8 | 5 | PLC8 | 7.8 |
| 704100800800090 | 8 | 40 | 4,000 | 8 | 8 | PLC8 | 12.7 |
| 704101000350090 | 10 | 63 | 6,300 | 12.6 | 3.5 | PLC10 | 9.3 |
| 704101000500090 | 10 | 63 | 6,300 | 12.6 | 5 | PLC10 | 12.6 |
| 704101000600090 | 10 | 63 | 6,300 | 12.6 | 6 | PLC10 | 15.3 |
| 704101000800090 | 10 | 63 | 6,300 | 12.6 | 8 | PLC10 | 19.7 |
| 704101001000090 | 10 | 63 | 6,300 | 12.6 | 10 | PLC10 | 23.9 |
| 704101300500090 | 13 | 100 | 10,000 | 21.2 | 5 | PLC13 | 21.6 |
| 704101300800090 | 13 | 100 | 10,000 | 21.2 | 8 | PLC13 | 32.8 |
| 704101301000090 | 13 | 100 | 10,000 | 21.2 | 10 | PLC13 | 40.6 |
| 704101600600090 | 16 | 160 | 16,000 | 32 | 6 | PLC16 | 39.7 |
| 704101600800090 | 16 | 160 | 16,000 | 32 | 8 | PLC16 | 51.3 |