

Lashing Chain POWERTEX PLC

Product information

POWERTEX



POWERTEX Lashing chains PLC are made of high strength Grade 8 round steel chains and latch hooks at each end.

The chains are designed to allow quick and safe hooking to the trailer and to the load to be secured.

- Safe – POWERTEX Lashing chains are strong and reliable and consist of EN standard compliant chains and hooks
- Lashing chains are made to EN 12195-3
- Black electrophoretic painted chains Grade 8 acc to EN818-2
- Red powder painted clevis hooks with heavy duty latches acc to EN1677-2
- Each lashing chain assembly is marked with a durable Aluminum Identification tag
- Intended to be used with POWERTEX load binder
- Multilanguage user manuals included

Material: High strength chain and hooks in Grade 8 acc to EN standard

Marking: According to standard, POWERTEX, Lashing capacity, "Lashing chain - Not for lifting!", Manufacturing date, Batch number. For 2-part lashing the STF is marked on the tensioner, not on the chain!

Temperature range: -40°C up to + 200°C.

Finish: Black electrophoretic painted chains and red powder painted hooks

Standard: EN 12195-3, EN 818-2, EN 1677-2

Note: For 2-part lashing the STF is marked on the tensioner, not on the chain

Warning: Not approved for lifting.



Part Code	Chain diameter mm	LC kN	LC daN	MBL ton	EWL m	Type	Weight	Delivery time
704101000350090	10	63	6,300	12.6	3.5	PLC10	9.3	3
704101000500090	10	63	6,300	12.6	5	PLC10	12.6	3
704100800800090	8	40	4,000	8	8	PLC8	12.7	3
704101000600090	10	63	6,300	12.6	6	PLC10	15.3	3
704101000800090	10	63	6,300	12.6	8	PLC10	19.7	3
704101300500090	13	100	10,600	21.2	5	PLC13	21.6	3
704101001000090	10	63	6,300	12.6	10	PLC10	23.9	3
704101300800090	13	100	10,600	21.2	8	PLC13	32.8	3
704101301000090	13	100	10,600	21.2	10	PLC13	40.6	3