



Round Sling Extreema® XS

Product information

The Extreema® XS sling is a compact high-strength round sling designed for lifting operations in confined or restricted spaces. It is used where traditional slings are too bulky or require larger hardware. Manufactured from HMPE, it combines high load capacity with a small diameter, enabling efficient and controlled lifting in tight environments.

WLL range: 3 – 20t

EWL range: 0,5m – 16m, (15t/20t can be made up to 65m)

When to choose this product

Best for:

- Lifting in confined spaces with limited clearance
- Applications requiring compatibility with standard shackles

Product benefits

- Compact diameter enables lifting in restricted or hard-to-reach areas
- D:d ratio 1:1 allows use with standard bow shackles
- HMPE construction provides high strength with low weight
- Lightweight design simplifies transport, handling, and storage
- Seamless sleeve supports durability and extended service life

Material: HMPE

Marking: According to standard, CE-marked

Temperature range: -40°C up to +70°C

Standard: EN 1492-2

except material

Safety factor: 7:1

Part code	WLL ton	EWL m	Colour
340500300200030	3	2	Yellow
340500300400030	3	4	Yellow
340500500100030	5	1	Red
340500500150030	5	1.5	Red
340500500200030	5	2	Red
340500500300030	5	3	Red
340500500400030	5	4	Red
340501000200030	10	2	Orange
340501000400030	10	4	Orange
340501001000030	10	10	Orange
340501000800030	10	8	Orange
340501000600030	10	6	Orange
340502000600030	20	6	Orange

Technical data

Extreema® XS roundsling**HMPE EXS**

WLL	SF	Core ø mm	Weight kg 3m EWL	p/m extra kg
3t	7	9	0,8	0,25
5t	7	14	1,35	0,43
10t	7	23	2	0,65
15t	7	31	3,5	1,15
20t	7	37	4,6	1,50