



Harness AVAO® FAST International Version

Product information

The AVAO FAST harness is specifically designed for workers at height. Its design is specific to work positioning and rope descent. Contoured foam on the semi-rigid waistbelt and leg loops provide comfort during use. The waistbelt features metal side attachment points, equipment loops, and tool holder slots, allowing the user to organize all the necessary equipment for a day of work. Adjustment is quick, easy, and convenient, with self-locking DOUBLEBACK buckles and FAST opening buckles.

Comfortable construction:

- Widely spaced shoulder straps reduce neck chafing
- Sliding straps provide more freedom and ease of movement
- All contact zones use contoured foam and are lined with breathable material, including the shoulder straps, waistbelt and leg loops, making it more comfortable to work and move around
- Semi-rigid waistbelt and leg loops provide optimal harness fit and support
- Metal side attachment points can be folded down to prevent them snagging accidentally when not in use
- Elastic leg loop bands (replaceable and available as an accessory) allow the harness to maintain the right adjustment whether the user is walking or suspended

Convenient and quick to adjust:

- Self-locking DOUBLEBACK buckles on the shoulder straps and waistbelt, and FAST opening buckles on the leg loops make adjustments quick, easy, and convenient
- Anti-slip devices installed on the DOUBLEBACK buckles help maintain the right adjustment throughout the workday

Easy to carry and organize equipment:

- Shoulder straps are equipped with a parking system for fall-arrest lanyard connectors, keeping the lanyard out of the user's way and the connectors within reach
- Metal ventral D ring is equipped with connection points to install a PODIUM or LITEPOD work seat
- Ventral connection point features a textile loop that allows the user to install a lanyard with a RING OPEN attachment ring
- Two side metal attachment points for connecting a positioning lanyard in double mode
- Five pre-shaped equipment loops with protective sheath
- Two slots for CARITool tool holders or the INTERFAST connection system

In the event of a fall on the dorsal attachment point, a red indicator appears, signaling that the harness should be retired

Material: Nylon, polyester, aluminum, steel

Marking: According to standard, CE-marked

Standard: EN 361, EN 813, EN 358

