

Thread Terminals Metric - TTM

Product information



TTM (Thread Terminals Metric) are stainless steel threaded terminals for pressing or swaging onto stainless steel wire rope. They are used to put tension on a wire, either with the help of nuts and washers or as part of a rigging screw.

Features:

- Wide range of sizes
- Available in right hand and left hand threads.
- Other sizes or UNF thread available on request
- Available with or without a nut.

Material: Stainless steel AISI 316.

Temperature range: -50°C to +100°C and briefly up to +200°C

Finish: High polished.

Note: Part codes ending in an "N" include a nut.

Warning: It is strongly recommended to lubricate threads first, before tensioning.

Part Code	Rope Ø range mm	MBL ton	Thread	G thread	D1 mm	D2 mm	L1 mm	L2 mm	L3 mm	KW mm	Weight kg/100pc	Delivery time
1207900306	3	1.2	R*	M6	3,3	6,35	100	38	48	5,0	2	7
1207900406	4	1.2	R*	M6	4,4	7,50	110	45	48	6,0	2.4	7
1207900406	4	1.7	R*	M8	4,4	7,50	117	45	57	6,0	3	7
1207900510	5	2.5	R*	M10	5,3	9,00	130	51	63	7,0	4.5	3
1207900610	6	3.5	R*	M10	6,5	12,58	145	64	63	11	8.4	7
1207900812	8	5.1	R*	M12	8,4	16,00	185	83	80	14	19.2	3
1207901016	10	9.4	R*	M16	10,5	17,80	210	89	100	15	35	3
1207901220	12	11.4	R*	M20	12,5	20,00	249	105	120	17	45	3

Blueprint

