

Wire Rope Clamp BG

Product information



General: Wire rope clamp type, approved for lifting. Requires fewer clamps per fixation, e.g. two wire clamps instead of four, for 16 mm cable. Symmetrical – cannot be wrongly fitted. The clamps ensure fixation of the wire to a degree of at least 90% of the minimum breaking load of the wire in accordance with the current European standard.

Design: Bases of cast steel.

Finish: Body Hot dip galvanized and bolt electro galvanized

Note: Follow the fitting instructions in the user manual before use. Not for use with compacted or hammered wire ropes.

| Part Code | Rope Ø range mm | Thread | No. of clamps when lifting* | Moment Nm | Weight kg/100pc | Delivery time |
|------------------|----------------------------|---------------|------------------------------------|----------------------|----------------------------|----------------------|
| 121100600050 | 5-6 | M6 | 2 | 9,5 | 9 | 3 |
| 121100800050 | 6.5-8 | M6 | 2 | 9,5 | 12 | 3 |
| 121101000050 | 8.5-10 | M8 | 2 | 22 | 20 | 3 |
| 121101250050 | 11-12.5 | M10 | 2 | 44 | 39 | 3 |
| 121101600050 | 13-16 | M12 | 2 | 75 | 72 | 3 |
| 121102000050 | 17-20 | M14 | 2 | 120 | 120 | 3 |
| 121102500050 | 21-25 | M18 | 2 | 260 | 280 | 3 |
| 121103400050 | 26-34 | M20 | 2 | 350 | 770 | 3 |