



Ferrule INOX Talurit®

Product information



These ferrules are normally used on stainless steel wire ropes to achieve the best possible resistance against corrosion.

Stainless steel Ferrule - recommended for machine pressing only. Suitable for long term use in salt water, waste water treatment and chemical processing.

Material: Stainless steel, AISI 316.

Note: See the manufacturer's product data sheet below for guidance on dimension selection. We do not guarantee strength of slings for lifting activities made of INOX ferrules. A termination performed according to our instructions will normally withstand a tensile strength of 90% of the minimum-breaking load (MBL) of the wire rope. Verifying tests must be done in order to find out the strength.

| Part Code | Ferrule size mm | Delivery time |
|------------------|----------------------------|----------------------|
| 120100100110 | 1 | 3 |
| 120100200110 | 2 | 3 |
| 120100250110 | 2.5 | 3 |
| 120100300110 | 3 | 3 |
| 120100400110 | 4 | 3 |
| 120100500110 | 5 | 3 |
| 120100600110 | 6 | 3 |
| 120100700110 | 7 | 3 |
| 120100800110 | 8 | 3 |
| 120100900110 | 9 | 7 |
| 120101000110 | 10 | 3 |
| 120101100110 | 11 | 3 |
| 120101200110 | 12 | 7 |
| 120101300110 | 13 | 3 |
| 120101400110 | 14 | 3 |
| 120101600110 | 16 | 3 |
| 120101800110 | 18 | 3 |