



Fibre Rope 3-Strand Movline Plus HBL

Product information

Movline Plus ropes are made from a high tenacity composite fiber extruded on a custom-built extrusion process. This extremely strong bi-polymer and its balanced twisted construction, result on a rope with good wear resistance and exceptional gripping capabilities that are enhanced by the outer fuzzy surface developed in use, also protecting the inner fibers against abrasion.

Advantages:

- High abrasion and wear resistance
- High strength floating line
- No water absorption
- Good UV resistance

Application areas:

- Tie up and Mooring lines
- General deck lines
- Towing lines

Technical Information:

- Specific Gravity: 0,94
- Melting Point: 165°C
- Elongation in % of the breaking load:

25% 6,0%

50% 11,5%

Material: Mixed Polyolefin

Marking: According to standard

Standard: EN ISO 10572

Part Code	Diameter mm	Min. Breaking force kN.	Length m	Colour	Rope ends	Weight kg/100m	Delivery time
300304802200250	48	417	220	Green	Plain ends	104	3
300305602200250	56	543	220	Green	Plain ends	142	3
300306002200250	60	613	220	Green	Plain ends	163	3
300306402200250	64	698	220	Green	Plain ends	186	3
300307202200250	72	878	220	Green	Plain ends	235	3