

Fibre Rope 3-Strand Movline Plus HBL

Product information



Movline Plus ropes are made from a high tenacity composite fiber extruded on a custom-built extrusion process. This extremely strong bi-polymer and its balanced twisted construction, result on a rope with good wear resistance and exceptional gripping capabilities that are enhanced by the outer fuzzy surface developed in use, also protecting the inner fibers against abrasion.

Advantages:

- High abrasion and wear resistance
- High strength floating line
- No water absorption
- Good UV resistance

Application areas:

- Tie up and Mooring lines
- General deck lines
- Towing lines

Technical Information:

- Specific Gravity: 0,94
- Melting Point: 165°C
- Elongation in % of the breaking load:

25% 6,0%

50% 11,5%

... [Read more](#)

Material: Mixed Polyolefin

Marking: According to standard

Standard: ISO 10572

Fibre Rope 3-Strand Movline Plus HBL

Technical data

Part code	Diameter mm	Min. breaking force kN	Length m	Colour	Rope ends	Weight kg/100m
300304802200250	48	417	220	Green	Plain ends	104
300305602200250	56	543	220	Green	Plain ends	142
300306002200250	60	613	220	Green	Plain ends	163
300306402200250	64	698	220	Green	Plain ends	186
300307202200250	72	878	220	Green	Plain ends	235