

Ship Buidling Clamp - IPBTO10



Product information

The IPBTO10 shipbuilding clamp is used as a temporary tackle eye in spaces which have been reinforced with HP (bulb) profiles such as engine rooms and shipsections. This clamp is fitted with a screwed spindle for easy attachment of the clamp. The moment a load is applied, the clamp is automatically fixed.

Features:

- Available in capacities of 1.5 through 6 metric tons.
- Wide variety of jaw openings available: HP 160mm to HP 430mm
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required.
- Individually Proof Tested to 2 times the Working Load Limit with certification.
- User manual with test certificate is included with each clamp.
- Maintenance and repair kits are available

Material: Alloy steel.

Marking: According to standard, CE-marked, WLL, Logo, Jaw opening, Serial number

Temperature range: -40°C up to +100°C

Standard: EN 13155

Part code	WLL ton	Model	Profile A*	B mm	C mm	D mm	E mm	F mm	Weight kg
502100150000280	1.5	1.5-IPBTO10	HP 160 - 240	137	188-209	129-150	68	81	4.3
502100300000280	3	3-IPBTO10	HP 240 - 320	137	188-217	145-174	68	78	6
502100600000280	6	6-IPBTO10	HP 300 - 430	185	255-297	195-236	98	102	13

Blueprint

