

## Horizontal Lifting Clamp IPHOZ



### Product information

The IPHOZ horizontal lifting clamp is to be used for lifting and transferring, in the horizontal position, of thin sheet and other materials that will sag or bend when lifted. These clamps must be used in pairs or more.

#### Features:

- Available in capacities of 0.75 through 15 metric tons
- Wide variety of jaw openings available: 0 to 60mm
- Welded alloy steel body for strength and smaller size. Forged alloy components, where required
- Individually Proof Tested to 2 times the Working Load Limit with certification
- User manual with test certificate is included with each clamp
- Maintenance and repair kits are available
- All sizes are RFID EQUIPPED

**Material:** Alloy steel

**Marking:** According to standard, CE-marked, WLL, Logo, Jaw opening, Serial number

**Temperature range:** -40°C up to +100°C

**Standard:** EN 13155

**Warning:** Only to be used in pairs.

Part code	WLL ton	Jaw width mm	Model	A mm	B mm	C mm	E mm	F mm	G mm	H mm	J mm	K mm	L mm	Weight kg
502100080300300	0.75	0-30	0.75-IPHOZ	0-30	94	16	16	70	118	81	12	31	12	3
502100150450300	1.5	0-45	1.5-IPHOZ	0-45	133	16	22	125	192	100	16	36	12	5.5
502100300450300	3	0-45	3-IPHOZ	0-45	137	20	26	125	200	120	20	48	10	8

## Blueprint

