



Swivel Eye / Eye Crosby S5

Product information

Design: Swivel with eyes equipped with tapered roller thrust bearing.

Features:

- Suitable for frequent rotation under load.
- All swivels individually Proof Tested to 2 times the Working Load Limit.
- Pressure lube fitting provided
- Other types and capacities up to 1250 t available on demand.

Marking: CE-marked

Note: Always check before use if your steel wire rope is suitable for use with a swivel.

Warning: Not to be used on demolition- (wrecking-) balls!

Safety factor: 5:1

| Part Code | WLL ton | Rope Ø mm | Swivel No | D mm | G mm | Q mm | R mm | S mm | T mm | Weight kg | Delivery time |
|--------------|---------|-----------|-----------|------|------|------|------|------|------|-----------|---------------|
| 422500500100 | 5 | 16 | 5-S-5 | 249 | 76 | 25.4 | 32.5 | 31.8 | 31.8 | 5.13 | 7 |
| 422500850100 | 8.5 | 19 | 8-S-5 | 302 | 102 | 31.8 | 35.8 | 41.1 | 38.1 | 13.3 | 7 |
| 422501000100 | 10 | 22 | 10-S-5 | 394 | 114 | 42.9 | 42.9 | 70 | 47.8 | 19.1 | 7 |
| 422501500100 | 15 | 26 | 15-S-5 | 416 | 127 | 49.3 | 51.5 | 70 | 54 | 22.2 | 7 |
| 422502500100 | 25 | - | 25-S-5 | 565 | 152 | 57 | 58.5 | 98.5 | 60.5 | 59 | 7 |

Blueprint

