

## **Swivel hook Crosby L-322 AN**

## **Product information**

## Features:

- Hoist hooks incorporate markings forged into the product which address two (2) QUIC-CHECK®
- Deformation Indicators -- Two strategically placed marks, one just below the shank or eye and the other on the hook tip, which allows for a QUIC-CHECK® measurement to determine if the throat opening has changed, thus indicating abuse or overload.
- Angle Indicators Indicates the maximum included angle which is allowed between two (2) sling legs in the hook. These indicators also provide the opportunity to approximate other included angles between two sling legs.

Material: Alloy steel
Marking: CE-marked

Note: This hook is a positioning device and is not intended to rotate under load.

Safety factor: 4:1

Grade: 8

| Part code    | WLL<br>ton | EWL<br>mm | A mm | B mm | C mm | D<br>mm | F<br>mm | G<br>mm | H<br>mm | L<br>mm | O*<br>mm | R<br>mm | S<br>mm | AA**<br>mm | Weight<br>kg |
|--------------|------------|-----------|------|------|------|---------|---------|---------|---------|---------|----------|---------|---------|------------|--------------|
| 420500320750 | 3.2        | 165       | 76   | 38.1 | 44.5 | 102     | 41.1    | 28.7    | 33.3    | 210     | 29.5     | 165     | 16      | 50.8       | 1.04         |
| 420500540750 | 5.4        | 191       | 89   | 41.7 | 50.8 | 123     | 51      | 36.6    | 41.4    | 246     | 35.8     | 191     | 19.1    | 63.5       | 2.25         |
| 420500800750 | 8          | 245       | 116  | 58   | 63.5 | 160     | 63.5    | 46      | 52.5    | 317     | 42.9     | 245     | 25.4    | 76.2       | 4.67         |
| 420501150750 | 11.5       | 289       | 127  | 62   | 70   | 192     | 76      | 57      | 67      | 375     | 56.5     | 289     | 28.7    | 101        | 8.8          |

## Blueprint

