

Master Link Hybrid MFH

Product information



Designed for crane hooks DIN 15401 and 15402. Designed for use with CL, CLD, CG and CGD. 3- and 4-leg chain slings require CLD / CGD.

... [Read more](#)

Material: Quenched and tempered alloy steel grade 10.

Marking: According to standard, code and grade.

Finish: Painted.

Standard: EN 1677


Warning: Not to be heat treated.

Safety factor: 5:1

Grade: 10

Master Link Hybrid MFH

Blueprint



Technical data

| Part code | Code | WLL ton | For chain, 1-leg mm | For chain, 2-leg mm | For chain, 3-4-leg mm | For crane hooks | D, mm | E mm | L mm | Weight kg |
|--------------|-------------|---------|---------------------|---------------------|-----------------------|-----------------|-------|------|------|-----------|
| 402100750120 | MFH-1310-10 | 7.5 | 13 | 10 | 8 | 12 | 22 | 125 | 230 | 2.1 |
| 402101000120 | MFH-1613-10 | 10 | 16 | 13 | 10 | 12 | 28 | 135 | 250 | 3.7 |
| 402101700120 | MFH-2016-10 | 17 | 20 | 16 | 13 | 16 | 32 | 135 | 280 | 5.3 |
| 402102800120 | MFH-2220-10 | 28 | 26 | 20 | 16 | 25 | 40 | 175 | 320 | 9.7 |