Lifting Solutions Group
Axel Johnson International

Safety Hook BK

Product information



Safety hook with eye connector.

... *Read more*

Material: Quenched and tempered alloy steel.
Marking: According to standard, code and grade.
Finish: Painted.
Standard: EN 1677
Warning: Not to be heat treated


Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Safety Hook BK

Blueprint



Technical data

Part code	Code	WLL ton	A mm	B mm	E mm	F mm	G mm	H mm	L mm	Weight kg
402300150140	BK-6-10	1.5	12	29	22	10	15	21	109	0.5
402300260140	BK-7/8-10	2.6	14	37	28	11	17	26	138	0.9
402300400140	BK-10-10	4	16	45	34	13	21	31	168	1.5
402300680140	BK-13-10	6.8	20	55	44	16	30	40	207	3
402301030140	BK-16-10	10.3	26	62	56	20	37	50	254	5.5
402301600140	BK-18/20-10	16	30	68	60	22	44	64	289	9
402302000140	BK-22-10	20	32	80	70	24	50	64	320	11.3
402302730140	BK-26-10	27.3	35	100	80	25	54	68	342	16.5

© November 2026 - All Rights Reserved