



## Swivel Safety Hook BKLK with Ball-bearing

### Product information

Safety hook with ball-bearing for 360° rotation under full WLL.

**Material:** Quenched and tempered alloy steel.

**Marking:** According to standard, code and grade.

**Finish:** Painted.

**Standard:** EN 1677

**Warning:** Not to be heat treated.

**Safety factor:** 4:1

**Grade:** 10

Part Code	Code	WLL ton	A mm	B mm	C mm	E mm	G mm	H mm	L mm	Weight kg	Delivery time
420500151330	BKLN-6-10	1.5	11	29	24	33	15	21	149	0.7	7
420500261330	BKLN-7/8-10	2.6	12	37	27	38	17	26	183	1.2	7
420500401330	BKLN-10-10	4	15	45	35	44	21	31	218	2	3
420500681330	BKLN-13-10	6.8	19	55	45	48	30	40	280	4	7
420501031330	BKLN-16-10	10.3	25	62	62	61	37	50	339	7.3	7
420501281330	BKLN-18/20-10 OS	12.8	35	68	88	80	46	64	395	13.5	3
420501601330	BKLN-18/20-10	16	31	68	60	72	44	62	368	11.5	7
420502731330	BKLN-26-10	27.3	45	100	110	102	54	68	486	26	7

## Blueprint

