Lifting Solutions Group
Axel Johnson International

Swivel Safety Hook BKLK with Ball-bearing

Product information



Safety hook with ball-bearing for 360º rotation under full WLL.

... *Read more*

Material: Quenched and tempered alloy steel.
Marking: According to standard, code and grade.
Finish: Painted.
Standard: EN 1677
Warning: Not to be heat treated.


Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

CERTEX | Lifting Solutions Group
Axel Johnson International

Swivel Safety Hook BKLK with Ball-bearing

Blueprint



Technical data

Part code	Code	WLL ton	A mm	B mm	C mm	E mm	G mm	H mm	L mm	Weight kg
420500151330	BKLK-6-10	1.5	11	29	24	33	15	21	149	0.7
420500261330	BKLK-7/8-10	2.6	12	37	27	38	17	26	183	1.2
420500401330	BKLK-10-10	4	15	45	35	44	21	31	218	2
420500681330	BKLK-13-10	6.8	19	55	45	48	30	40	280	4
420501031330	BKLK-16-10	10.3	25	62	62	61	37	50	339	7.3
420501281330	BKLK-18/20-10 OS	12.8	35	68	88	80	46	64	395	13.5
420501601330	BKLK-18/20-10	16	31	68	60	72	44	62	368	11.5
420502731330	BKLK-26-10	27.3	45	100	110	102	54	68	486	26

© November 2026 - All Rights Reserved