



Sling Hook EK

Product information

Sling hook with eye connector.

Material: Quenched and tempered alloy steel.

Marking: According to standard, code and grade.

Finish: Painted.

Standard: EN 1677

Warning: Not to be heat treated.

Safety factor: 4:1

Grade: 10

| Part code | Code | WLL ton | B mm | E mm | F mm | G mm | H mm | L mm | Weight kg |
|--------------|----------|---------|------|------|------|------|------|------|-----------|
| 402300150190 | EK-6-10 | 1.5 | 29 | 23 | 10 | 17 | 20 | 93 | 0.4 |
| 402300400190 | EK-10-10 | 4 | 41 | 34 | 14 | 23 | 30 | 134 | 0.9 |
| 402300680190 | EK-13-10 | 6.8 | 49 | 44 | 18 | 28 | 38 | 166 | 2 |
| 402301030190 | EK-16-10 | 10.3 | 61 | 56 | 22 | 36 | 47 | 203 | 3.3 |
| 402302000190 | EK-22-10 | 20 | 82 | 64 | 31 | 43 | 67 | 267 | 8.5 |
| 402302730190 | EK-26-10 | 27.3 | 95 | 66 | 32 | 51 | 75 | 301 | 12.1 |

Blueprint

