



## Swivel Latch Hook LKNK

### Product information

Swivel latch hook with ball bearing for 360° rotation under full WLL.

**Material:** Quenched and tempered alloy steel.

**Marking:** According to standard, code and grade.

**Finish:** Painted.

**Standard:** EN 1677

**Warning:** Not to be heat treated.

**Safety factor:** 4:1

**Grade:** 10

| Part Code    | Code        | WLL ton | A mm | B mm | C mm | E mm | G mm | H mm | L mm | Weight kg | Delivery time |
|--------------|-------------|---------|------|------|------|------|------|------|------|-----------|---------------|
| 420500260580 | LKNK-7/8-10 | 2.6     | 12   | 28   | 28   | 38   | 18   | 24   | 154  | 0.9       | 3             |
| 420500400580 | LKNK-10-10  | 4       | 15   | 35   | 35   | 44   | 23   | 31   | 191  | 1.6       | 3             |
| 420500680580 | LKNK-13-10  | 6.8     | 19   | 40   | 45   | 48   | 28   | 38   | 236  | 3.3       | 3             |
| 420501030580 | LKNK-16-10  | 10.3    | 25   | 53   | 62   | 61   | 34   | 43   | 293  | 5.6       | 7             |
| 420502000580 | LKNK-22-10  | 20      | 35   | 74   | 80   | 80   | 43   | 67   | 400  | 15.1      | 7             |

## Blueprint

