

Arctic Shackle No 856 Gunnebo - Safety Bolt



Product information

Adverse weather and rough sea conditions in combination with extremely low temperatures, as often encountered in the North Sea for instance, places tough requirements on the Products used. Gunnebo Industries has a range of shackles specially designed for these conditions.

Approved according to: DNV 2.7-1

Material: Special Alloy Steel, quenched and tempered.

Marking: According to standard, CE-marked

Temperature range: -40°C up to 200°C

Finish: All parts hot dip galvanized, brown colour making

Standard: EN 13889, US. FED. SPEC. RR-C-271

Safety factor: 6:1

Grade: 8

Part code	WLL ton	a mm	c mm	d mm	d1 mm	d2 mm	e mm	Weight kg
420100200420	2	21	47	1/2" - 13	16	33	33	0.42
420100330420	3.25	27	60	5/8" - 16	19	40	42	0.7
420100480420	4.75	31	71	3/4" - 19	22	48	49	1.2
420100650420	6.5	37	84	7/8" - 22	25	52	60	1.7
420100850420	8.5	43	95	1" - 25	28	60	68	2.5
420100950420	9.5	46	108	1 1/8" - 28	32	64	74	3.4
420101200420	12	52	119	1 1/4" - 32	35	72	83	4.8
420101350420	13.5	57	132	1 3/8" - 35	38	76	89	7
420101700420	17	60	146	1 1/2" - 38	42	84	98	9
420102500420	25	74	178	1 3/4" - 45	50	105	127	15
420103500420	35	83	197	2" - 50	57	116	138	21
420105500420	55	105	260	2 1/2" - 65	70	145	180	39

Blueprint

