

## Dee Shackle No 835, Gunnebo - Safety Bolt



### Product information

**Approved according to:** DNV 2.7-1

**Forging tolerances:** +-5% on inside width/length.

**Material:** High tensile steel, quenched and tempered.

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to 200°C

**Finish:** All parts hot dip galvanized, brown painted bolts/pins on top of galv.

**Standard:** EN 13889, US. FED. SPEC. RR-C-271

**Safety factor:** 6:1

Part Code	WLL ton	a mm	c mm	d mm	d1 mm	d2 mm	Weight kg	Delivery time
420100330380	3.25	27	51	5/8" - 16	19	40	0.6	3
420100480380	4.75	31	60	3/4" - 19	22	48	1.1	3
420100650380	6.5	37	71	7/8" - 22	25	52	1.5	3
420100850380	8.5	43	81	1" - 25	28	60	2.2	3
420100950380	9.5	46	90	1 1/8" - 28	32	64	3.1	3
420101200380	12	52	100	1 1/4" - 32	35	72	4.2	3
420101350380	13.5	57	111	1 3/8" - 35	38	76	5.6	3
420101700380	17	60	122	1 1/2" - 38	42	84	7.5	3
420102500380	25	74	149	1 3/4" - 45	50	105	13	3

## Blueprint

