

## Bow Shackle No 854, Gunnebo - Screw Pin



### Product information

**Approved according to:** DNV 2.7-1

**Forging tolerances:** +/-5% on inside width/length.

**Material:** High tensile steel, quenched and tempered.

**Marking:** According to standard, CE-marked

**Temperature range:** -20°C up to 200°C

**Finish:** All parts hot dip galvanized, brown painted bolts/pins on top of galv.

**Standard:** EN 13889, US. FED. SPEC. RR-C-271

**Safety factor:** 6:1

**Grade:** 6

Part Code	WLL ton	a mm	c mm	d mm	d1 mm	d2 mm	e mm	Weight kg	Delivery time
420100200400	2	21	47	1/2" - 13	16	33	33	0.37	3
420100330400	3.25	27	60	5/8" -16	19	40	42	0.65	3
420100480400	4.75	31	71	3/4" - 19	22	48	49	1.1	3
420100650400	6.5	37	84	7/8" - 22	25	52	60	1.5	3
420100850400	8.5	43	95	1" - 25	28	60	68	2.21	3
420100950400	9.5	46	108	1 1/8" - 28	32	64	74	3.1	3
420101200400	12	52	119	1 1/4" -32	35	72	83	4.2	3
420101350400	13.5	57	132	1 3/8" - 35	38	76	89	6	3
420101700400	17	60	146	1 1/2" - 38	42	84	98	8	7
420102500400	25	74	178	1 3/4" - 45	50	105	127	13.5	3
420103500400	35	83	197	2" - 50	57	112	138	19	3

## Blueprint

