

## Chain Block KITO M3

### Product information



KITO M3 Series Chain Hoists are built with premium grade components for long life in demanding industrial and contracting applications. M3 lever hoists feature double-reduction gearing for reduced size and weight.

Safe, reliable mechanical brake activates instantly, holds the load securely.

Double reduction gearing for a smaller hoist that requires minimum power to operate.

Spring loaded free-wheel for fast, easy load chain free-wheeling.

Open load sheave allows easy inspection and cleaning without dismantling the unit

Maintenance free sealed gears and brake protected against damage from dust and water.

... [Read more](#)

**Material:** High impact steel housing, chain grade 10.

**Marking:** According to standard, CE-marked, WLL, code.

**Temperature range:** -40°C up to +60°C


**Finish:** Painted.

**Standard:** AS 1418.2

**Safety factor:** 4:1

## Chain Block KITO M3

### Blueprint



### Technical data

Part code	WLL ton	Lifting height m	Number of falls	Load chain mm	a mm	b mm	d mm	e mm	f mm	g mm	s mm	t mm	u mm	v mm	w mm	x mm	Weight kg
500100050250050	0.5	2.5	1	5	158	161	2,500	69	99	27	35.5	12.1	17	77	35	89	10
500100050600050	0.5	6	1	5	158	161	2,500	69	99	27	35.5	12.1	17	77	35	89	10
500100100250050	1	2.5	1	6,3	162	161	2,500	71	99	29	42.5	16	21.8	93	41	101	11.5
500100100450050	1	4.5	1	6.3	162	161	2,500	71	99	29	42.5	16	21.8	93	41	101	11.5
500100150250050	1.5	2.5	1	7,1	171	182	2,500	78	112	34	47.5	19.5	26.5	106	47	119	14.5
500100200300050	2	3	1	8	185	202	3,000	87	125	36	50	21.8	30	116	49	124	20
500100200600054	2	6	1	8	182	202	3,000	87	125	36	50	21.8	30	116	49	124	20
500100200450050	2	4.5	1	8	182	202	3,000	87	125	36	50	21.8	30	116	49	124	23.45
500100300300050	3	3	2	7,1	171	235	3,100	78	162	42.5	56	27.2	37.5	138	57	148	24
500100500300050	5	3	2	9	192	282	3,600	91	194	46.5	63	34.5	47.5	161	67.5	172	41
500101000500050	10	5	4	9	192	438	4,200	111	308	72.5	85	47.5	63	231	97.5	295	83