

## Swivel Self Looking Hook DA-027N

---

### Product information



With Ball Bearing, which preforms full swivel under load.

Fatigue rated to 20,000 cycles at 1.5 times the Working Load Limit (WLL)

Designed with recessed trigger and ball bearing. Providing the locking mechanism being protected against inadvertent opening due to entanglement with any obstruction during lifting.

Latch mechanism is self locking under loading.

[... Read more](#)

---

**Material:** Forged alloy steel, quenched and tempered with grade 8 character.


**Marking:** According to standard

**Standard:** Norsok R-002 Approved, DNV 2.7-1 Approved, EN 1677-3

**Safety factor:** 5:1

## Swivel Self Looking Hook DA-027N

### Blueprint



### Technical data

Part code	WLL ton	WLL ton Safety Factor 4:1	A mm	B mm	D mm	H, mm	K mm	Pmm mm	T mm	Weight kg
420500530970	5.3	6.7	61	50	23	39	283	51	30	5
420500800970	8	10	74	82	25	49	361	60	36	8.1
420501280970	12.8	16	74	82	25	65	387	70	53	13
420501520970	15.2	19	97	95	33	63	457	80	49	20
420502120970	21.2	26.5	123	115	42	69	535	99	56	32.7
420502520970	25.2	31.5	123	115	42	81	583	120	63	41