



Swivel Self Locking Hook DA-027N

Product information

With Ball Bearing, which preforms full swivel under load.

Fatigue rated to 20,000 cycles at 1.5 times the Working Load Limit (WLL)

Designed with recessed trigger and ball bearing. Providing the locking mechanism being protected against inadvertent opening due to entanglement with any obstruction during lifting.

Latch mechanism is self locking under loading.

Material: Forged alloy steel, quenched and tempered with grade 8 character.

Marking: According to standard

Standard: Norsok R-002 Approved, DNV 2.7-1 Approved, EN 1677-3

Safety factor: 5:1

| Part code | WLL ton | WLL ton Safety Factor 4:1 | A mm | B mm | D mm | H mm | K mm | P mm | T mm | Weight kg |
|--------------|---------|---------------------------|------|------|------|------|------|------|------|-----------|
| 420500530970 | 5.3 | 6.7 | 61 | 50 | 23 | 39 | 283 | 51 | 30 | 5 |
| 420500800970 | 8 | 10 | 74 | 82 | 25 | 49 | 361 | 60 | 36 | 8.1 |
| 420501280970 | 12.8 | 16 | 74 | 82 | 25 | 65 | 387 | 70 | 53 | 13 |
| 420501520970 | 15.2 | 19 | 97 | 95 | 33 | 63 | 457 | 80 | 49 | 20 |
| 420502120970 | 21.2 | 26.5 | 123 | 115 | 42 | 69 | 535 | 99 | 56 | 32.7 |
| 420502520970 | 25.2 | 31.5 | 123 | 115 | 42 | 81 | 583 | 120 | 63 | 41 |

Blueprint

