Lifting Solutions Group
Axel Johnson International

Chain Short Link VIS 200

Product information

- Manufactured from special analysis alloy steel.
- Quenched and tempered before proof testing.
- Working load limit up to 40 tonnes.
- 25% higher strength than Grade 80.

... *Read more*



Marking: According to standard, At least every 20th link, or at least one link per meter, is labeled with manufacturer, grade and traceability code.
Temperature range: -29°C up to 205°C
Finish: Blue painted
Standard: EN 818-2


Safety factor: 4:1
Grade: 10

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Chain Short Link VIS 200

Blueprint



Technical data

Part code	Chain diameter mm	WLL ton	Min. breaking force kN	Pitch Length mm	d mm	p mm	w1mm mm	w2 mm	Weight kg
203500600000160	6	1.4	56.5	18	6	18	7.8	22.2	0.83
203500800000160	8	2.5	101	24	8	24	10.4	29.6	1.51
203501000000160	10	4	157	30	10	30	13	37	2.27
203501300000160	13	6.7	265	39	13	39	16.9	48.1	3.9
203501600000160	16	10	402	48	16	48	20.8	59.2	5.79
203502000000160	20	16	628	60	20	60	26	74	8.9
203502200000160	22	19	760	66	22	66	28.6	81.4	11.4
203502600000160	26	26.5	1,060	78	26	78	33.8	96.2	16
203503200000160	32	40	1,610	96	32	96	41.6	118	24.1

© November 2026 - All Rights Reserved