

Trygg Shackle Liner

Product information

This shackle liner is a supplemental product used to increase the contact diameter in round- and webbing slings.

Before use:

Check if labelling is visible and readable and that the information matches the product.

Make sure there are no deformations, notch/impact damage, cracks, heat damage/welding spatter or chemical damage.

If damaged, replace with new!

Equipment use:

- Secure the liner with strips to prevent fall risk hazard. This will also keep the sling in place. Please assemble at ground level.
- Match colour model with the correct size shackle, and never assemble liner on top of liner!
- Never use Trygg shackle liner if there are visible cracks or damages, or if it's being overloaded!
- · Lift calmly and without jerking.
- Only one sling per shackle liner.
- Use the same slings from the same manufacturer, as the requirements for minimum contact diameter may vary for different manufacturers.

After use:

Inspected the liner for wear and tear, cracks or other damages that may have occurred during use.

Other info:_

Trygg shackle liner is not subject to yearly inspection as it is only an accessory that increases the diameter of the shackles.

Temperature range: -40°C up to +50°C

Part Code	Description	Colour	Delivery time
4297F3250T	Fits 3,25 ton H-shackle from Greenpin and GN Rope Fittings	Green	3
4297F4750T	Fits 4,75 ton H-shackle	yellow	3
4297F6500T	Fits 6,5 ton H-shackle	Red	3