CERTEX | Lifting Solutions Group
Axel Johnson International

Lever Hoist Powertex PLH-S1

Product information



Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Compact, lightweight construction.
- Durable all steel construction with powder coated finish and plated frame components.
- Safe, well covered automatic load reaction brake.
- European made COROLIM® protected load chain.
- Corrosion resistance of the chain is equivalent to ISO944-9 C5High / ISO9223 C3
- Bottom hook with ball bearing.
- RFID equipped (chip) for easy service and inspection.
- QR code for on-site access to Multilanguage user manuals.
- User manuals in 14 languages included.
- Testcertificate enclosed.

... *Read more*

Marking: According to standard, CE-mark
Temperature range: -10°C up to +50°C.
Standard: EN 13157, EN 818-7


Safety factor: 4:1

© November 2026 - All Rights Reserved

Lifting Solutions Group
Axel Johnson International

Lever Hoist Powertex PLH-S1

Blueprint



Technical data

Part code	WLL ton	Lifting height m	Number of falls	A mm	B mm	C mm	D mm	E mm	H min mm	Ø mm mm	Weight kg
500500600150090	6	1.5	2	208	120	230	388	43	615	43	29.5

© November 2026 - All Rights Reserved