

GB Instruction for use
NO Bruksanvisning

POWERTEX Load Binder PLB



User Manual



POWERTEX Load Binder Instruction for use (GB) (Original instructions)



WARNING

- Failure to follow the regulations of this instruction for use may cause serious consequences as risk of injury.
- Read and understand these instructions before use.

Information

Check the current regulations as required to achieve the approved cargo securing. For transport within Europe the securing of cargo in most cases must meet the requirements of EN 12195-1.

Applications

PowerTex load binders are used for easy and safe tightening of chain for lashing applications.

Design

PowerTex load binders are manufactured from drop forged steel. The hooks have been designed to support the chain in the best way, and to reduce chain wear. The hooks are fitted with a safety pin, to keep the chain in place.

PowerTex load binders have been designed to be operated using one hand.

Each load binder is marked with:

- Lashing capacity e.g. LC 40kN
- Minimum breaking load e.g. 80,4kN
- Manufacturer's symbol e.g. SQQ
- Chain diameter in mm and inches e.g. 8mm and 5/16"
- G80 e.g. Grade 80
- Traceability code e.g. E1
- Warning not for lifting or hoisting applications

Finish

PowerTex load binders are painted red.


Instructions for use

ALWAYS inspect load binder before use, to ensure that:

- load binders are free from deformations, nicks, gouges and cracks;
- all markings are legible;
- a load binder with the correct Lashing Capacity has been selected, with respect to chain size and load to be lashed. For further details we refer to EN 12195-3, standard for Lashing Chains;

During use:

- Make sure the load binder can operate in a straight line
- Attach the load binder to the chain without twisting the chain
- Secure the chain in the shortening hooks using the locking devices
- Tighten the load binder by hand without use of extension with standard hand force of 50 daN."
- ensure that the handle or any other locking system cannot vibrate out of position;
- always keep yourself out of the path of the moving handle;
- if the handle of a lever type load binder is released by hand, make sure you use an open hand under the handle and push upward. Do not close your hand around the handle. Move the handle with caution since it may whip as it comes free;



Maintenance

Load binders must be regularly inspected in accordance with the safety standards given in the country of use. This is required because the products in use may be affected by wear, misuse, overloading etc. which may lead to deformation and alteration of the material structure. Regularly lubricate all moving parts of a load binder to extend product life and reduce wear.



WARNING

NEVER use load binder for lifting or hoisting applications.

NEVER use load binder while standing on the load.

NEVER repair or reshape a load binder by welding, heating or bending as this may affect the lashing capacity.

NEVER side load the load binder, since load binders are suitable for in-line use only.

NEVER use handle extensions, always hand tighten only.



End of use/Disposal

PowerTex load binders shall always be sorted / scrapped as general steel scrap.

The supplier will assist you with the disposal, if required.

Disclaimer

We reserve the right to modify product design, materials, specifications or instructions without prior notice and without obligation to others.

If the product is modified in any way, or if it is combined with a non-compatible product/component, we take no responsibility for the consequences in regard to the safety of the product

POWERTEX lastebånd

Bruksanvisning (NO)



ADVARSEL

- Unnlatelse av å følge forskriftene i denne bruksanvisningen vil kunne føre til alvorlige konsekvenser, slik som fare for personskade.
- Les og sett deg inn i denne anvisningen før bruk.

Informasjon

Kontroller gjeldende regelverk etter behov for å oppnå godkjent sikring av last. For transport i Europa oppfyller sikring av last i de fleste tilfeller kravene i EN 12195-1.

Bruksformål

Powertex lastebånd brukes til enkel og sikker stramming av kjetting for bruksformål knyttet til surring.

Design

Powertex lastebånd er produsert av senkesmidd stål. Krokene er utformet for å støtte kjettingen optimalt og for å redusere slitasje på kjettingen. Krokene er utstyrt med en sikkerhetsplugg for å holde kjettingen på plass.

Powertex lastebånd er laget for å kunne brukes med bare én hånd.

Hvert lastebånd er merket med følgende:

- Slyngekapasitet, f.eks. LC 40 kN
- Minimal bruddbelastning, f.eks. 80,4 kN
- Produsentens symbol, f.eks. SQQ
- Kjettingdiameter i mm og tommer, f.eks. 8 mm og 5/16"
- G80 f.eks. materialklasse 80
- Sporbarhetskode, f.eks. E1
- Advarsel ikke for bruksformål knyttet til løfting eller heising

Overflate

Powertex lastebånd er malt røde.


Bruksanvisninger

Sjekk ALLTID lastebånd før bruk, for å sikre at:

- Sperrebjørnen er uten deformasjoner, hakk, riller og sprekker;
- All merking er leselig
- Et lastebånd med riktig slyngekapasitet er valgt mht. kjettingens dimensjoner og den lasten som skal surres. For ytterligere informasjon, se EN 12195-3, normen for slyngekjettinger

Ved bruk:

- * Sørg for at sperrebjørnen kan brukes uhindret i en rett linje
- * Fest sperrebjørnen til kjettingen uten å vri kjettingen
- * Fest kjettingen i innkorkningskroken og sett på låsemekanisme
- * Stram sperrebjørnen for hånd med vanlig håndkraft på 50 daN uten å bruke forlengelse av håndtaket som vektstang
- * Sørg for at verken håndtaket eller andre låsemekanismer kan vibrere ut av riktig stilling.
- * Hold deg alltid ute av veien for håndtaket
- * Dersom håndtaket på en sperrebjørn med skrallestammer løsnes for hånd, må man sørge for å bruke åpen hånd under håndtaket og skyve oppover. Ikke bruk en lukket hånd rundt håndtaket. Beveg håndtaket med forsiktighet da det kan slå opp når det frigjøres.



Vedlikehold

Lastebånd må sjekkes jevnlig iht. sikkerhetsnormene som gjelder i det landet der båndene brukes. Dette kreves fordi produktene som brukes vil kunne bli påvirket av slitasje, misbruk, overbelastning osv. som vil kunne føre til deformering og endring i materialstrukturen. Smør jevnlig alle lastebåndets bevegelige deler for å forlenge produktets levetid og redusere slitasje.



ADVARSEL

Bruk ALDRI lastebåndet til formål knyttet til løfting eller heising
Bruk ALDRI lastebåndet mens du står oppå lasten.

Reparér ALDRI og gjenoppsett ALDRI et lastebåndets form ved å sveise det, varme det opp eller bøye det, ettersom det vil kunne påvirke surrekapasiteten.

Belast ALDRI siden på lastebåndet, ettersom lastebånd kun egner seg til bruk på linje.

Bruk ALDRI håndtaksforlengere, og stram alltid kun manuelt.



Når bruken opphører/Avhendelse

Powertex lastebånd skal alltid sorteres/avfallshåndteres som generelt stålskrap.

Leverandøren vil hjelpe deg med avhendelse, om nødvendig.

Ansvarsfraskrivelse

Vi forbeholder os retten til å endre produktdesign, materialer, spesifikasjoner eller anvisninger uten varsel og uten forpliktelse overfor andre.

Hvis produktet er endret på noen måte, eller hvis det er kombinert med et ikke-kompatibelt produkt/komponent, vil ikke vi kunne ta på os ansvar for konsekvenser med hensyn til produktets sikkerhet.

CertMax+

The CertMax+ system is a unique leading edge certification management system which is ideal for managing a single asset or large equipment portfolio across multiple sites. Designed by the Lifting Solutions Group, to deliver optimum asset integrity, quality assurance and traceability, the system also improves safety and risk management levels.

CertMax


Marking

Standard: EN 12195-3



Warning tag

The warning tag shows some specific and important situations, in which you must pay special attention, when using POWERTEX Load Binder.



User Manuals

You can always find the valid and updated User Manuals on the web. The manual is updated continuously and valid only in the latest version.

NB! The English version is the Original instruction.

The manual is available as a download under the following link:
www.powertex-products.com/manuals



Product compliance and conformity

SCM Citra OY
Asessorinkatu 3-7
20780 Kaarina
Finland
www.powertex-products.com



POWERTEX

www.powertex-products.com